

Cancelled

Title: FUSES, SUBMINIATURE, CURRENT-LIMITING,
HIGH RELIABILITY, SPACE USE,
DETAIL SPECIFICATION FOR

Document number: JAXA-QTS-2210/101C

Cancellation date: 15 July 2020

JAXA
JAPAN AEROSPACE EXPLORATION AGENCY

Registration No. 1236

JAXA-QTS-2210/101C

31 January 2019

Superseding

JAXA-QTS-2210/101B

Cancelled

31 January 2019

FUSES,
SUBMINIATURE, CURRENT-LIMITING,
HIGH RELIABILITY, SPACE USE,
DETAIL SPECIFICATION FOR

Prepared and Established by
TATEYAMA KAGAKU DEVICE TECHNOLOGY CO., LTD.

Issued by Japan Aerospace Exploration Agency

This document is the English version of JAXA QTS/ADS which was originally written and authorized in Japanese and carefully translated into English for international users. If any question arises as to the context or detailed description, it is strongly recommended to verify against the latest official Japanese version.

The release date of the English version of this specification: January 17, 2022

JAXA-QTS-2210/101C 31 January 2019		J A X A Parts Specification	Page	– i –
Revision Log				
Rev.	Date	Description		
NC	7 June 2011	Original		
A	15 March 2012	1) Cover sheet: Changed the corporate name from TATEYAMA KAGAKU IND. Co., LTD. to TATEYAMA KAGAKU DEVICE TECHNOLOGY CO., LTD. due to the name change. 2) Paragraph 1.3, Table 2: Corrected the nominal resistance of JAXA2210/101-A72V1.5AL from 97.0 – 163mΩ to 70.0 – 163mΩ.		
B	21 April 2014	Paragraph 4.3.1 Added a paragraph Clarified the configuration of inspection lot for quality conformance inspection. Paragraphs 4.2 and 4.3 Specified the test circuit for overload interrupt.		
C	31 Jan. 2019	Cover: Changed corporate name. Table 4 Modified the mass due to the change of resin materials. Style J1: 0.43 to 0.47 → 0.46 to 0.50 Style J2: 1.95 to 2.15 → 2.00 to 2.20 Paragraph 4.4.1: Specified the handling of products stored for a long time at manufacturer's site.		
		Remainder intentionally left blank.		

JAXA-QTS-2210/101C 31 January 2019	J A X A Parts Specification	Page	– ii –
Contents			
1. GENERAL		1	
1.1 Scope		1	
1.2 Part Number		1	
1.3 Ratings		1	
2. APPLICABLE DOCUMENTS.....		2	
3. REQUIREMENTS		2	
3.1 Performance		3	
4. QUALITY ASSURANCE PROVISIONS.....		5	
4.1 In-Process Inspection		5	
4.2 Qualification Test		5	
4.3 Quality Conformance Inspection		7	
4.3.1 Sample		7	
4.4 Long-Term Storage.....		10	
4.4.1 Handling of Products Stored for a Long Time at Manufacturer's Site		10	
4.4.2 Storage by Purchasers		10	
4.5 Changes of Test and Inspection		11	
5. PREPARATION FOR DELIVERY		11	
6. NOTES.....		11	

JAXA-QTS-2210/101C 31 January 22019	J A X A Parts Specification	Page	– 1 –		
<div>FUSES, SUBMINIATURE, CURRENT-LIMITING, HIGH RELIABILITY, SPACE USE, DETAIL SPECIFICATION FOR</div>					
1. GENERAL					
1.1 Scope					
This specification establishes the detailed requirements for JAXA-QTS-2210, the high reliability, subminiature, current-limiting fuses (hereinafter referred to as "fuses") to be used for electronic equipment installed on spacecrafts such as satellites.					
1.2 Part Number					
The part numbers for the fuses covered in this specification shall be assigned as the following example. Refer to Table 1 for details.					
Example:					
JAXA ⁽¹⁾ 2210/101	-	<div>A</div>	<div>72V</div>	<div>1A</div>	<div>L</div>
		Characteristic	Rated voltage	Rated current	Terminal structure
Note: ⁽¹⁾ “JAXA” indicates the common part for space use and may be abbreviated to “J.”					
Table 1. Part Number					
Item	Applicable paragraph of JAXA-QTS-2210	Specification			
Characteristic	1.4.1	A: Fast acting			
Rated voltage	1.4.2	72V, 126V			
Rated current	1.4.3	1A, 1.5A, 2A, 3A, 5A, 7.5A, 10A, 15A			
Terminal structure	1.4.4	L: Tough pitch copper, solder finish of 1.52μm thickness or more			
1.3 Ratings					
The ratings are shown in Table 2.					

Table 2. Ratings

Part number	Rating			Pre-arcing time (m sec) ⁽³⁾			Operating temperature range	Rated breaking capacity	Style ⁽⁴⁾
	Voltage (V)	Current ⁽¹⁾ (A)	Nominal resistance ⁽²⁾ (mΩ)	Test current 250%	Test current 400%	Test current 600%			
JAXA 2210/101-A72V1AL	72	1.0	110-220	10.0-300	1.00-15.0	0.15-3.00	-55°C to +125°C	1,000A	J1
JAXA 2210/101-A72V1.5AL	72	1.5	70.0-163						
JAXA 2210/101-A72V2AL	72	2.0	45.0-75.0						
JAXA 2210/101-A72V3AL	72	3.0	20.0-43.8						
JAXA 2210/101-A72V5AL	72	5.0	12.0-22.5						
JAXA 2210/101-A72V7.5AL	72	7.5	8.20-13.8						
JAXA 2210/101-A72V10AL	72	10.0	6.30-10.7						
JAXA 2210/101-A72V15AL	72	15.0	4.00-7.00	10.0-300	0.75-15.0	0.10-3.00			J2
JAXA 2210/101-A126V1AL	126	1.0	90.0-270						
JAXA 2210/101-A126V3AL	126	3.0	20.0-95.0						
JAXA 2210/101-A126V5AL	126	5.0	12.0-40.0						

Notes: ⁽¹⁾ Loads shall be derated when the case temperature exceeds +25°C.
⁽²⁾ Resistance at 25°C.
⁽³⁾ The maximum pre-arcing time at -55°C with 250% loads shall be as specified below.
 1.0A: 10 sec., 1.5A: 10 sec., 2.0A: 10 sec., 3.0A or more: 5 sec.
⁽⁴⁾ Refer to Figure 2 and Table 4.




Figure 1. Derating Curve

2. APPLICABLE DOCUMENTS

The applicable documents shall be as specified in paragraph 2.1 of JAXA-QTS-2210.

3. REQUIREMENTS

The requirements shall be as follows and as specified in paragraph 3 of JAXA-QTS-2210.

JAXA-QTS-2210/101C 31 January 22019		J A X A Parts Specification	Page	– 3 –																																																																																																																																																																					
<p>3.1 Performance</p> <p>The performances are shown in Table 3.</p> <p style="text-align: center;">Table 3. Performance</p> <table> <tr> <th colspan="2">Item</th><th>Requirements paragraph of JAXA-QTS-2210</th><th colspan="2">Performance</th></tr> <tr> <td colspan="2">Materials</td><td>3.3</td><td colspan="2">As specified in Table 5.</td></tr> <tr> <td colspan="2">Design and construction</td><td>3.4</td><td colspan="2">As specified in Figure 3.</td></tr> <tr> <td colspan="2">Externals, dimensions and marking</td><td>3.5</td><td colspan="2"></td></tr> <tr> <td></td><td>Externals and markings</td><td>3.5.1</td><td colspan="2">As specified in JAXA-QTS-2210. Marking shall be as shown in Figure 4.</td></tr> <tr> <td></td><td>Dimensions and weight</td><td>3.5.2</td><td colspan="2">As specified in Figure 2 and Table 4.</td></tr> <tr> <td colspan="2">Workmanship</td><td>3.6</td><td colspan="2">As specified in JAXA-QTS-2210.</td></tr> <tr> <td colspan="2">Electrical performance</td><td>3.8</td><td colspan="2"></td></tr> <tr> <td></td><td>Burn-in</td><td>3.8.1</td><td colspan="2">Allowable voltage drop change: within $\pm 10\%$</td></tr> <tr> <td></td><td>Resistance</td><td>3.8.2</td><td colspan="2">As specified in Table 2.</td></tr> <tr> <td></td><td>Current-carrying capacity</td><td>3.8.3</td><td colspan="2">5.0A or less: $+85^{\circ}\text{C}$ max. 7.5A or more: $+120^{\circ}\text{C}$ max.</td></tr> <tr> <td></td><td>Dielectric withstanding voltage</td><td>3.8.4</td><td colspan="2">Resistance after test: As specified in Table 2.</td></tr> <tr> <td></td><td>Overload interrupt</td><td>3.8.5</td><td colspan="2">Pre-arcing time: As specified in Table 2.</td></tr> <tr> <td></td><td>Short circuit interrupt</td><td>3.8.6</td><td colspan="2">As specified in JAXA-QTS-2210.</td></tr> <tr> <td></td><td>Insulation resistance</td><td>3.8.7</td><td colspan="2">As specified in JAXA-QTS-2210.</td></tr> <tr> <td></td><td>Resistance-temperature coefficient</td><td>3.8.8</td><td colspan="2">$+3500\pm 700\text{ppm}/^{\circ}\text{C}$</td></tr> <tr> <td colspan="2">Mechanical performance</td><td>3.9</td><td colspan="2"></td></tr> <tr> <td></td><td>Terminal strength</td><td>3.9.1</td><td colspan="2">Allowable resistance change: within $\pm 10\%$</td></tr> <tr> <td></td><td>Solderability</td><td>3.9.2</td><td colspan="2">As specified in JAXA-QTS-2210.</td></tr> <tr> <td></td><td>Resistance to soldering heat</td><td>3.9.3</td><td colspan="2">Allowable resistance change: within $\pm 10\%$</td></tr> <tr> <td colspan="2">Environmental performance</td><td>3.10</td><td colspan="2"></td></tr> <tr> <td></td><td>High-frequency vibration</td><td>3.10.1.1</td><td colspan="2">Allowable resistance change: within $\pm 10\%$</td></tr> <tr> <td></td><td>Random vibration</td><td>3.10.1.2</td><td colspan="2">Allowable resistance change: within $\pm 10\%$</td></tr> <tr> <td></td><td>Shock</td><td>3.10.2</td><td colspan="2">Allowable resistance change: within $\pm 10\%$</td></tr> <tr> <td></td><td>Thermal shock[I]</td><td>3.10.3.1</td><td colspan="2">As specified in JAXA-QTS-2210.</td></tr> <tr> <td></td><td>Thermal shock[II]</td><td>3.10.3.2</td><td colspan="2">Allowable resistance change: within $\pm 10\%$</td></tr> <tr> <td></td><td>Salt spray (corrosion)</td><td>3.10.4</td><td colspan="2">Allowable resistance change: within $\pm 10\%$</td></tr> <tr> <td></td><td>Moisture resistance</td><td>3.10.5</td><td colspan="2">Allowable resistance change: within $\pm 15\%$</td></tr> <tr> <td></td><td>Low-temperature operation</td><td>3.10.6</td><td colspan="2">Allowable resistance change: within $\pm 10\%$</td></tr> <tr> <td></td><td>Thermal vacuum</td><td>3.10.7</td><td colspan="2">Pre-arcing time: As specified in Table 2. Allowable resistance change: within $\pm 10\%$</td></tr> <tr> <td></td><td>Resistance to solvents</td><td>3.10.8</td><td colspan="2">Not applicable as this fuse apply laser marking.</td></tr> <tr> <td colspan="2">Durability</td><td>3.11</td><td colspan="2"></td></tr> <tr> <td></td><td>Steady-State life</td><td>3.11.1</td><td colspan="2">Allowable resistance change: within $\pm 10\%$</td></tr> </table>					Item		Requirements paragraph of JAXA-QTS-2210	Performance		Materials		3.3	As specified in Table 5.		Design and construction		3.4	As specified in Figure 3.		Externals, dimensions and marking		3.5				Externals and markings	3.5.1	As specified in JAXA-QTS-2210. Marking shall be as shown in Figure 4.			Dimensions and weight	3.5.2	As specified in Figure 2 and Table 4.		Workmanship		3.6	As specified in JAXA-QTS-2210.		Electrical performance		3.8				Burn-in	3.8.1	Allowable voltage drop change: within $\pm 10\%$			Resistance	3.8.2	As specified in Table 2.			Current-carrying capacity	3.8.3	5.0A or less: $+85^{\circ}\text{C}$ max. 7.5A or more: $+120^{\circ}\text{C}$ max.			Dielectric withstanding voltage	3.8.4	Resistance after test: As specified in Table 2.			Overload interrupt	3.8.5	Pre-arcing time: As specified in Table 2.			Short circuit interrupt	3.8.6	As specified in JAXA-QTS-2210.			Insulation resistance	3.8.7	As specified in JAXA-QTS-2210.			Resistance-temperature coefficient	3.8.8	$+3500\pm 700\text{ppm}/^{\circ}\text{C}$		Mechanical performance		3.9				Terminal strength	3.9.1	Allowable resistance change: within $\pm 10\%$			Solderability	3.9.2	As specified in JAXA-QTS-2210.			Resistance to soldering heat	3.9.3	Allowable resistance change: within $\pm 10\%$		Environmental performance		3.10				High-frequency vibration	3.10.1.1	Allowable resistance change: within $\pm 10\%$			Random vibration	3.10.1.2	Allowable resistance change: within $\pm 10\%$			Shock	3.10.2	Allowable resistance change: within $\pm 10\%$			Thermal shock[I]	3.10.3.1	As specified in JAXA-QTS-2210.			Thermal shock[II]	3.10.3.2	Allowable resistance change: within $\pm 10\%$			Salt spray (corrosion)	3.10.4	Allowable resistance change: within $\pm 10\%$			Moisture resistance	3.10.5	Allowable resistance change: within $\pm 15\%$			Low-temperature operation	3.10.6	Allowable resistance change: within $\pm 10\%$			Thermal vacuum	3.10.7	Pre-arcing time: As specified in Table 2. Allowable resistance change: within $\pm 10\%$			Resistance to solvents	3.10.8	Not applicable as this fuse apply laser marking.		Durability		3.11				Steady-State life	3.11.1	Allowable resistance change: within $\pm 10\%$	
Item		Requirements paragraph of JAXA-QTS-2210	Performance																																																																																																																																																																						
Materials		3.3	As specified in Table 5.																																																																																																																																																																						
Design and construction		3.4	As specified in Figure 3.																																																																																																																																																																						
Externals, dimensions and marking		3.5																																																																																																																																																																							
	Externals and markings	3.5.1	As specified in JAXA-QTS-2210. Marking shall be as shown in Figure 4.																																																																																																																																																																						
	Dimensions and weight	3.5.2	As specified in Figure 2 and Table 4.																																																																																																																																																																						
Workmanship		3.6	As specified in JAXA-QTS-2210.																																																																																																																																																																						
Electrical performance		3.8																																																																																																																																																																							
	Burn-in	3.8.1	Allowable voltage drop change: within $\pm 10\%$																																																																																																																																																																						
	Resistance	3.8.2	As specified in Table 2.																																																																																																																																																																						
	Current-carrying capacity	3.8.3	5.0A or less: $+85^{\circ}\text{C}$ max. 7.5A or more: $+120^{\circ}\text{C}$ max.																																																																																																																																																																						
	Dielectric withstanding voltage	3.8.4	Resistance after test: As specified in Table 2.																																																																																																																																																																						
	Overload interrupt	3.8.5	Pre-arcing time: As specified in Table 2.																																																																																																																																																																						
	Short circuit interrupt	3.8.6	As specified in JAXA-QTS-2210.																																																																																																																																																																						
	Insulation resistance	3.8.7	As specified in JAXA-QTS-2210.																																																																																																																																																																						
	Resistance-temperature coefficient	3.8.8	$+3500\pm 700\text{ppm}/^{\circ}\text{C}$																																																																																																																																																																						
Mechanical performance		3.9																																																																																																																																																																							
	Terminal strength	3.9.1	Allowable resistance change: within $\pm 10\%$																																																																																																																																																																						
	Solderability	3.9.2	As specified in JAXA-QTS-2210.																																																																																																																																																																						
	Resistance to soldering heat	3.9.3	Allowable resistance change: within $\pm 10\%$																																																																																																																																																																						
Environmental performance		3.10																																																																																																																																																																							
	High-frequency vibration	3.10.1.1	Allowable resistance change: within $\pm 10\%$																																																																																																																																																																						
	Random vibration	3.10.1.2	Allowable resistance change: within $\pm 10\%$																																																																																																																																																																						
	Shock	3.10.2	Allowable resistance change: within $\pm 10\%$																																																																																																																																																																						
	Thermal shock[I]	3.10.3.1	As specified in JAXA-QTS-2210.																																																																																																																																																																						
	Thermal shock[II]	3.10.3.2	Allowable resistance change: within $\pm 10\%$																																																																																																																																																																						
	Salt spray (corrosion)	3.10.4	Allowable resistance change: within $\pm 10\%$																																																																																																																																																																						
	Moisture resistance	3.10.5	Allowable resistance change: within $\pm 15\%$																																																																																																																																																																						
	Low-temperature operation	3.10.6	Allowable resistance change: within $\pm 10\%$																																																																																																																																																																						
	Thermal vacuum	3.10.7	Pre-arcing time: As specified in Table 2. Allowable resistance change: within $\pm 10\%$																																																																																																																																																																						
	Resistance to solvents	3.10.8	Not applicable as this fuse apply laser marking.																																																																																																																																																																						
Durability		3.11																																																																																																																																																																							
	Steady-State life	3.11.1	Allowable resistance change: within $\pm 10\%$																																																																																																																																																																						




Figure 2. Dimensional Drawing


Table 4. Dimension and Weight

Style	Dimension (mm)							Weight (g) (typ.)
	A	B	C	D (min.)	E	F ⁽¹⁾	G (max.) (⁽²⁾)	
J1	7.00 ^{+0.1} _{-0.3}	5.40 ^{+0.1} _{-0.3}	3.50 ^{+0.1} _{-0.3}	40.0	4.00±0.05	0.60±0.05	5.00	0.46 to 0.50
J2	9.00 ^{+0.1} _{-0.3}	9.30 ^{+0.1} _{-0.3}	5.00 ^{+0.1} _{-0.3}	57.0	5.00±0.05	1.20±0.1	5.00	2.00 to 2.20

Notes: ⁽¹⁾ Dimensions after solder coating.

⁽²⁾ Length of uncoated part of the lead from fuse body.

Cross-section of entire fuse



Cross-section of internal chip




Figure 3. Construction

Table 5. Materials

Construction	Material
1. Case material	PPS resin
2. Substrate	Alumina 96% Thickness: J1) 0.500mm, J2) 0.635mm
3. Solder joint	Solder: Sn 8% / Ag 2% / Pb 90%
4. Lead terminal	Core: C1100W (Cu 99.9%) Ni plating 3μm / Gold plating 0.5μm / Solder coat finish (Sn 63% / Pb 37%)
5. Protective coating	Low-melting-point glass
6. Upper glass	Low-melting-point glass
7. Fuse element	Gold-based thick film conductive material
8. Lower glass	Low-melting-point glass
9. Electrode pad	Ni




Figure 4. Markings

4. QUALITY ASSURANCE PROVISIONS

4.1 In-Process Inspection


The in-process inspection shall be performed in accordance with paragraph 4.3 of JAXA-QTS-2210.

4.2 Qualification Test

The qualification test shall be performed in accordance with paragraph 4.4 of JAXA-QTS-2210 and as specified in Table 6.

JAXA-QTS-2210/101C 31 January 22019			J A X A Parts Specification		Page	– 6 –
Table 6. Qualification Test						
Test			JAXA-QTS-2210		Pass/Fail criteria	
Group	Order	Item	Requirements paragraph	Test method paragraph	No. of samples	No. of defectives allowed
I	1	Externals, dimension and marking	3.5	4.6.2	85	0
	2	Thermal shock [I]	3.10.3.1	4.6.6.3.1		
	3	Burn-in	3.8.1	4.6.4.1		
	4	Resistance	3.8.2	4.6.4.2		
	5	Current-carrying capacity	3.8.3	4.6.4.3		
	6	Dielectric withstanding voltage	3.8.4	4.6.4.4		
II	1	X-ray inspection	3.6.1	4.6.3.1	85	0
	2	DPA	3.6.2	4.6.3.2	3	0
III	1	Resistance-temperature coefficient	3.8.8	4.6.4.8	18	0
	2	Resistance to solvents	Not applicable			
	3	Terminal strength	3.9.1	4.6.5.1		
	4	Overload interrupt (-55°C, +125°C) ⁽²⁾	3.8.5	4.6.4.5		
	5	Insulation resistance	3.8.7	4.6.4.7		
	6	Solderability	3.9.2	4.6.5.2		
IV	1	Low-temperature operation	3.10.6	4.6.6.6	18	0
	2	Steady-state life	3.11.1	4.6.7.1		
	3	Overload interrupt (+25°C) ⁽²⁾	3.8.5	4.6.4.5		
	4	Insulation resistance	3.8.7	4.6.4.7		
V	1	Thermal vacuum	3.10.7	4.6.6.7	8	0
VI	1	Short circuit interrupt	3.8.6	4.6.4.6	4	0
VII	1	Salt spray (corrosion)	3.10.4	4.6.6.4	4	0
	2	Overload interrupt (+25°C) (600%) ⁽²⁾	3.8.5	4.6.4.5		
	3	Insulation resistance	3.8.7	4.6.4.7		
VIII	1	Moisture resistance	3.10.5	4.6.6.5	12	0
	2	Resistance to soldering heat	3.9.3	4.6.5.3		
	3	High-frequency vibration	3.10.1.1	4.6.6.1.1		
	4	Random vibration	3.10.1.2	4.6.6.1.2		
	5	Shock	3.10.2	4.6.6.2		
	6	Current-carrying capacity	3.8.3	4.6.4.3		
	7	Overload interrupt (+25°C) ⁽²⁾	3.8.5	4.6.4.5		
	8	Insulation resistance	3.8.7	4.6.4.7		
IX	1	Thermal shock [II]	3.10.3.2	4.6.6.3.2	18	0
	2	Overload interrupt (+25°C) ⁽²⁾	3.8.5	4.6.4.5		
	3	Insulation resistance	3.8.7	4.6.4.7		
-	1	Materials	3.3	—	⁽¹⁾	

Note2: ⁽¹⁾ Documents shall be submitted to prove that the samples satisfy the design specification.
⁽²⁾ The drawing of the test circuit for overload interrupt is shown in Figure 5.



Notes:

- (1) A battery, or power supply with which the impedance is less than 10% of the total impedance of the circuit shall be used.
- (2) A switch for high current without a risk of contact bounce shall be used.
- (3) A oscillograph or an equivalent measuring circuit for recording current shall be used.
- (4) The same resistance value as the test fuse shall be set in order to obtain prospective current.

Figure 5. Test Circuit for Overload Interrupt of Qualification Test

4.3 Quality Conformance Inspection

The quality conformance inspection shall be performed in accordance with paragraph 4.5 of JAXA-QTS-2210 and as specified in Tables 7, 8, and 9.

4.3.1 Sample

The inspection lot for quality conformance inspection shall consist of the following items.

a) Qualify conformance inspection (Group A)

The samples with the identical characteristics and ratings under the identical production conditions shall be used.

b) Qualify conformance inspection (Group B and C)

Sampling from the lot which passed the Group A inspection, Group B and C inspections shall be performed with the following combination .

- 1) Characteristic A, Style J1, rated voltage 72V at any rated current between 1.0 to 7.5A
- 2) Characteristic A, Style J2, rated voltage 72V at any rated current between 10.0 to 15.0A
- 3) Characteristic A, Style J2, rated voltage 126V at any rated current between 1.0 to 5.0A

Table 7. Quality Conformance Inspection (Group A)

Test			JAXA-QTS-2210		Pass/Fail criteria	
Group	Order	Item	Requirements paragraph	Test method paragraph	No. of samples	No. of defectives allowed
A1	1	X-ray inspection	3.6.1	4.6.3.1	100%	N/A
A2	1	Thermal shock [I]	3.10.3.1	4.6.6.3.1	100%	0
	2	Burn-in	3.8.1	4.6.4.1		
	3	Resistance	3.8.2	4.6.4.2		
A3	1	Externals, dimensions and marking	3.5	4.6.2	AQL ⁽¹⁾ 1.0%	
A4	1	Current-carrying capacity (+25°C)	3.8.3	4.6.4.3	21 ⁽²⁾	0
	2	Dielectric withstanding voltage	3.8.4	4.6.4.4		
	3	Overload interrupt (+25°C) ⁽³⁾	3.8.5	4.6.4.5		
	4	Insulation resistance	3.8.7	4.6.4.7		
A5	1	Terminal strength	3.9.1	4.6.5.1	4	0
	2	Solderability	3.9.2	4.6.5.2		
A6	1	DPA	3.6.2	4.6.3.2	3	0

Notes: ⁽¹⁾ The acceptance quality level (AQL) is based on a single sampling plans for normal inspection, specified in JIS Z 9015-1, Attachment Table 2-A.

(2) Samples shall be selected from the both ends of truncated distribution based on the voltage drop after burn-in test.

⁽³⁾ The drawing of the test circuit for overload interrupt is shown in Figure 6.

Table 8. Quality Conformance Inspection (Group B)


Test			JAXA-QTS-2210		Pass/fail criteria	
Group	Order	Item	Requirement paragraph	Test method paragraph	No. of samples	No. of defectives allowed
B1	1	Low temperature operation	3.10.6	4.6.6.6	12	0
	2	Steady-state life	3.11.1	4.6.7.1		
	3	Overload interrupt (+25°C) ⁽¹⁾	3.8.5	4.6.4.5		
	4	Insulation resistance	3.8.7	4.6.4.7		
B2	1	Short circuit Interrupt	3.8.6	4.6.4.6	4	0
B3	1	Resistance–temperature coefficient	3.8.8	4.6.4.8	6	0
	2	Terminal strength	3.9.1	4.6.5.1		
	3	Overload interrupt (+25°C) (600%) ⁽¹⁾	3.8.5	4.6.4.5		
	4	Insulation resistance	3.8.7	4.6.4.7		
	5	Resistance to solvents	Not applicable			
B4	1	Resistance to soldering heat	3.9.3	4.6.5.3	4	0
	2	High frequency vibration	3.10.1.1	4.6.6.1.1		
	3	Random vibration	3.10.1.2	4.6.6.1.2		
	4	Shock	3.10.2	4.6.6.2		
B5	1	Salt spray (corrosion)	3.10.4	4.6.6.4	4	0
	2	Overload interrupt (+25°C) (600%) ⁽¹⁾	3.8.5	4.6.4.5		
	3	Insulation resistance	3.8.7	4.6.4.7		
B6	1	Moisture resistance	3.10.5	4.6.6.5	4	0
	2	Current-carrying capacity	3.8.3	4.6.4.3		

Note: ⁽¹⁾ The drawing of the test circuit for overload interrupt is shown in Figure 6.

Table 9. Quality Conformance Inspection (Group C)

Test			JAXA-QTS-2210		Pass/fail criteria	
Group	Order	Item	Requirement paragraph	Test method paragraph	No. of samples	No. of defectives allowed
C1	1	Thermal vacuum	3.10.7	4.6.6.7	8	0
C2	1	Thermal shock [II]	3.10.3.2	4.6.6.3.2	18	0
	2	Overload interrupt (+25°C) ⁽¹⁾	3.8.5	4.6.4.5		
	3	Insulation resistance	3.8.7	4.6.4.7		

Note: ⁽¹⁾ The drawing of the test circuit for overload interrupt is shown in Figure 6.



(1) A specific constant test current shall be applied to the fuse using an electronic load device.

Figure 6. Test Circuit for Overload Interrupt of Quality Conformance Inspection

4.4 Long-Term Storage

Long-term storage shall be in accordance with paragraph 4.7 of JAXA-QTS-2210 and as specified below.

4.4.1 Handling of Products Stored for a Long Time at Manufacturer's Site

The fuses stored more than 24 months after Quality Conformance Inspection (Group A) shall be inspected either 100 % or by sampling for the following test items in accordance with Tables 7 and 8, and accepted products can only be shipped. Sampling inspection shall be performed per production lot and the result of the inspection will be valid for 24 months.

The re-inspection date shall be printed on the package, storage box, or the certificate of the inspection attached to the products.

a) 100% inspection:

- 1) Resistance (Group A2-3)
- 2) Externals and markings (Group A3-1)

b) Sampling inspection:

- 1) Current-carrying capacity (Group A4-1)
- 2) Dielectric withstanding voltage (Group A4-2)
- 3) Overload interrupt (Group A4-3)
- 4) Insulation resistance (Group A4-4)
- 5) Solderability (Group A5-2)
- 6) Resistance to soldering heat (Group B4-1)

4.4.2 Storage by Purchasers

The products shall be stored at room temperature (15 to 30°C) and at the normal humidity (25 to 85%RH) in the package provided by the manufacturer. The product shall be stored in a clean place free of direct sunlight and hazardous gases such as chlorine and sulfur.

JAXA-QTS-2210/101C 31 January 22019	J A X A Parts Specification	Page	– 11 –
<div data-bbox="188 230 699 264" data-label="Section-Header"> <p>4.5 Changes of Test and Inspection</p> </div> <div data-bbox="280 277 1374 353" data-label="Text"> <p>There is no change to the test or inspection from the quality conformance inspection specified in JAXA-QTS-2210.</p> </div> <div data-bbox="188 383 687 416" data-label="Section-Header"> <p>5. PREPARATION FOR DELIVERY</p> </div> <div data-bbox="250 430 1295 465" data-label="Text"> <p>Preparation for delivery shall be as specified in paragraph 5 of JAXA-QTS-2210.</p> </div> <div data-bbox="250 470 767 506" data-label="Text"> <p>The packaging form shall be as follows.</p> </div> <div data-bbox="250 510 521 546" data-label="Text"> <p>a) Palette packaging</p> </div> <div data-bbox="188 575 352 609" data-label="Section-Header"> <p>6. NOTES</p> </div> <div data-bbox="250 622 839 658" data-label="Text"> <p>Refer to the paragraph 6 of JAXA-QTS-2210.</p> </div>			